

UpadIV-S


FLEXIBLE SOLUTION

- Support $\pm 40^\circ$
- Minimum 1.4m diameter cylinder, only 9 cabinets
- Perfect 'S' shape

Creative Flexible Rental Solution

The UpadIV-S is specially designed for creative stage display. Its flexible and soft body is designed for customers' imaginative creative display. It can be perfectly realized whether it is "C" shape or "S" shape display splicing. The cabinet of the XS series is made of ultra-high-strength aluminum alloy, which ensures lightness and flexibility while maintaining high strength.

Creative Shapes




Cylinder

Minimum diameter of 1.4



Concave & Convex

Perfect "S" shape of a single cabinet



Round-corner & Square Cylinder

More scene application options

Contact Us

844.263.3675 | www.unilumin-usa.com

Find Us @UniluminUSA



SPECIFICATIONS

Parameter	Value
Pixel Pitch	2.6mm
LED Type	3-in-1 Black SMD
Brightness	1000 cd/m ²
Pixel Density	147,456 pixels/m ²
Pixels Per Panel	192×192 pixels
Module Size	W500mm×H125mm
Panel Size	W500mm×H500mm×D80mm
Weight	7.7 kg/panel
Maintenance	Rear
Ingress Protection	IP30
Curve	(Convex) -40°~+40°(Concave)
Aspect Ratio	1:1
Environment	Environment Indoor
Material	Die-cast Aluminum
Calibration	Brightness and Chroma
Brightness Control	Manual/Automatic
Color Temperature	2,000K-9,300K Adjustable
Horizontal Viewing Angle	160°
Vertical Viewing Angle	160°
Contrast Ratio	5,000:1
Input Power <Max>	160 W/panel
Input Power <Typical>	55 W/panel
Input Voltage	100~240 VAC
Processing Depth	14 bit
Scan Method	1/16
Refresh Rate	3840@60 Hz
Video Frame Rate	50/60 Hz
Input Power Frequency	50~60 Hz
LED Life Time	100,000 Hours
Operating Temperature/Humidity	-10°C~+45°C/10~80%RH
Storage Temperature/Humidity	-20°C~+55°C/10~80%RH
Standard Mounting Configuration	Hanging, Stacking